Shielded Power Inductors – HC1049



- Designed foruse in multi-phase VRM/VRD regulators and high current/high frequency DC/DC converters.
- Requires only 70 mm² of board space; can handle up to 61 A.

Core material Ferrite
Core and winding loss
Terminations RoHS compliant matte tin over nickel over copper. Other terminations available at additional cost.
Weight 1.25 – 1.30 g
Ambient temperature –40°C to +85°C with (40°C rise) Irms current.
Maximum part temperature +125°C (ambient + temp rise).
Storage temperature Component: –40°C to +125°C. Tape and reel packaging: –40°C to +80°C
Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles
Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)
Failures in Time (FIT) / Mean Time Between Failures (MTBF) 38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332
Packaging 250/7″ reel; 1000/13″ reel Plastic tape: 24 mm wide, 0.35 mm thick, 12 mm pocket spacing, 5.08 mm pocket depth
PCB washing Tested to MIL-STD-202 Method 215 plus an additional aqueous wash.

Part number[1]	L ±20%[2] (µH)	DCR (mOhms)[3] typ	DCR (mOhms)[3] max	SRF typ[4] (MHz)	Isat[5] (A)	Irms[6] (A)
HC1049-750ML_	0.075	0.230	0.246	200	61.0	66.0
HC1049-101ML_	0.100	0.230	0.246	145	50.0	66.0
HC1049-121ML_	0.125	0.230	0.246	140	37.0	66.0
HC1049-151ML_	0.150	0.230	0.246	133	30.0	66.0
HC1049-231ML_	0.230	0.230	0.246	70	25.5	66.0

Irms Testing

Irms testing was performed on 0.75 inch wide × 0.25 inch thick copper traces in still air.

Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.

1. When ordering, please specify **termination** and **packaging** codes:

HC1049-151MLC

Termination: **L** = RoHS compliant matte tin over nickel over copper. **Special order: T** = RoHS tin-silver-copper (95.5/4/0.5) or **S** = non-RoHS tin-lead (63/37).

Packaging: **C** = 7″ machine-ready reel. EIA-481 embossed plastic tape (250 per full reel).
B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added ($25 charge), use code letter C instead.
D = 13″ machine-ready reel. EIA-481 embossed plastic tape (1000 per full reel). Factory order only, not stocked.

2. Inductance tested at 100 kHz, 0.1 Vrms using an Agilent/HP 4263B LCR meter or equivalent.
3. DCR is measured on a micro-ohmmeter at points indicated in the dimensional diagram.
4. SRF measured with coils connected in series using an Agilent/HP 8753ES network analyzer or equivalent.
5. DC current at 25°C that causes a 20% (typ) inductance drop from its value without current.
6. Current that causes a 40°C temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.
7. Electrical specifications at 25°C.

Refer to Doc 362 “Soldering Surface Mount Components” before soldering.



Dimensions are in inches / mm



▲Points used for measuring DCR

Recommended Land Pattern



PulseGM
www.pulsegm.com
China +86-0755-21055287
Sales@pulsegm.com

© PulseGM Inc. 2019
This product may not be used in medicalor high risk applications without prior PulseGM approval.
Specification subject to change without notice.
Please check web site for latestinformation.

Shielded Power Inductors - HC1049 Series

L vs Current



L vs Frequency



ESR vs Frequency



© PulseGM Inc. 2019
This product may not be used in medicalor high risk applications without prior PulseGM approval.
Specification subject to change without notice.
Please check web site for latestinformation.